FieldLink process networking AS-Interface

Masters and gateways

Model number GW458094A GW458118A (ETL)

AS-Interface to DeviceNet gateway

The AS-Interface/DeviceNet gateway serves to connect the AS-Interface to a DeviceNet network. The gateway acts as a complete master for the AS-Interface network and as a slave for DeviceNet (group 2 slave only). All AS-Interface functions can be called up via DeviceNet.

Features

- · Duplicate address detection
- · AS-Interface peripheral fault diagnostics
- Version 3.0 master-compatible with all 2.0-3.0 slaves and 7.3 profile analog modules
- Serial diagnostics port: see SW462008A for software and cable
- ETL approved for Class I Division 2 (GW458118A)






Specifications	
AS-Interface master version	3.0
Interface	DeviceNet (5 pin plug)
Operating current	200mA (from AS-Interface)
Operating voltage	30 VDC AS-Interface voltage
AS-Interface cycle time	Cycle time = 150 microsec. x (AS-Interface Slaves +2)
Displays	LCD display DeviceNet voltage on, green LED AS-Interface power on, green LED Module/Net Status (MNS), green/red LED Serial communication active, green LED Configuration error, red LED AS-Interface voltage normal, green LED AS-Interface normal operation, green LED Automatic address program enabled, green LED Master in configuration mode, yellow LED
Operating temperature	0° to +55°C (+32° to +131°F)
Storage temperature	-25° to +85°C (-13° to +185°F)
Housing	Stainless steel, DIN rail mounting
Dimensions (L, W, H)	120mm, 85mm, 83mm
Ingress protection	IP20, field enclosure required
Weight	520g (1.1 pounds)
Approvals (GW458118A)	ETL approved Class I Division 2, groups A,B,C,D







Schematic drawing




Graphical display

The interactive graphical display on this gateway enables the entire AS-Interface network to be commissioned and the connected devices to be completely tested without a PC, PLC or host system. It also enables the user to complete all tasks previously requiring the "AS-Interface Control Tools" software package or hand-held. This allows for simpler and faster commissioning.

Features

18

- Set device addresses
- · Test inputs and outputs
- Perform network diagnostics
- · View error counter



Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Vanha Porvoontie 229 01380 Vantaa, Finland flowcontrol@valmet.com +358 10 417 5000 valmet.com/flowcontrol

Valmet Flow Control Inc. Stonel product center

26271 US Hwy 59, Fergus Falls, MN 56537 USA. Tel. +1 218 739 5774. sales.stonel@valmet.com valmet.com/flowcontrol



