



# Stonel™ product mapping

## Food and Beverage



### Valve communication and control

1/4-Turn On/Off  
(2-way & 3-way available)

Linear (diaphragm)  
(on/off & 4-20mA available)

#### Pilot Solenoid Valve

**Integral**  
(single & dual pilots available),  
(external override available)

**Panel Mounted**

**Integral**  
(on/off & 4-20mA available)

**Panel Mounted**  
(on/off only)

#### Platform



Axiom AN series



Axiom ANX series



Eclipse EC series



Prism PI series



Prism PI series

#### Hazardous Area Classification

CID2 AN\_ \_  
CID1 I.S. AN45

CID2 ANX\_ \_  
CID1 XP ANX\_ \_

CID2 EC\_ \_  
CID1 I.S. EC45

CID2 PI\_ \_  
CID1 I.S. PI45S1NS

CID2 PI\_ \_  
CID1 I.S. PI45S11S

Stonel™ Axiom™



Stonel™ Eclipse™



Stonel™ Prism™



	1/4-turn		Linear
	Axiom	Eclipse	Prism
<b>Specifications</b>			
Non-contact solid state sensors with LEDs and 5 year warranty	●	●	●
2-wire solid state sensors are both AC and DC compatible	●	●	●
PNP/NPN self calibration 3-wire unit, <b>patented technology</b>		●	
<b>Feedback "Input" options</b>			
On/off (Discrete Input = DI)	●	●	●
4-20mA (Analog Input = AI)			Optional
<b>Control "Output" options</b>			
On/off (Discrete Output = DO)	●		Optional
4-20mA (Analog Output = AO)			Optional
<b>Optional communication technology</b>			
AS-interface	versions 3 & 5	●	●
DeviceNet	●	EN & EG	●
IO-Link		●	●
Diagnostics available as an option	●	●	●
Red/green LEDs are coordinated with red/green mechanical visual indicator (Prism; green only)	●	●	●
Push button set/calibration and wireless calibration option	●	●	●
Integral solenoid	Standard		Optional
Rebreather (maintains clean/dry instrument air on both sides of the actuator)	●		
General purpose and Division 2 (nonincendive) standard; Division 1 (I.S.) optional	●	●	●
Pin-connector options (not viable in CID1 XP applications)	AN only	●	●
NPT conduit options	●	●	●
Screw on cover allows quicker access for maintenance needs; no special tools required	●	●	●
Epoxy coated anodized aluminum and stainless steel hardware	●		
Stainless steel enclosure and hardware	ANX only		
Polycarbonate materials with stainless steel hardware		●	●
5 year bumper to bumper warranty (includes solenoid and mounting hardware)	●		



Subject to change without prior notice.

Neles, Neles Easyflow, Jamesbury, Stonel, Valvcon and Flowrox, and certain other trademarks, are either registered trademarks or trademarks of Valmet Oyj or its subsidiaries in the United States and/or in other countries.

Valmet Flow Control Oy

Vanha Porvoontie 229, 01380 Vantaa, Finland.

flowcontrol@valmet.com

+358 10 417 5000

www.valmet.com/flowcontrol